



TECHNICAL DATA SHEET

Issued: 09 Aug 2026

Doc Ref: NPC-TDS-ANTI-MOIST

Ultrafine - Our Own Manufacturing

Anti Moisture Powder

In-house formulated moisture-control powders combining silica gel, talc, bentonite clay, activated carbon and calcium carbonate for anti-clumping and product stability.

Typical Properties

Parameter	Typical Value
Appearance	Fine white/off-white powder
Moisture Absorption Capacity	High - formulation dependent
Bulk Density	0.4-0.6 g/cm ³
Particle Size	<= 75 micron (200 mesh)
pH (10% aqueous)	6.0-8.0
Loss on Drying	<= 1.5%

Values shown are typical/indicative for the product family and are not to be construed as a specification. Confirm certificate-of-analysis figures for the specific batch/grade at time of order.

Available Grades

- Polyshine Ultrafine
- Premium Ultrafine
- Rose Brand Ultrafine
- SPL Ultrafine
- Super Shakti L. Powder

Recommended Applications

Packaged Goods . Industrial Storage . Compounding

Packaging, Storage & Handling

Supplied in multi-ply paper/HDPE bags or drums as per grade (typical 25 kg net, other pack sizes on request). Store in a cool, dry, well-ventilated area away from direct sunlight and moisture. Keep containers closed when not in use. Handle with standard industrial PPE; consult the Safety Data Sheet (SDS) for full handling and disposal guidance.

Note: This sheet is a general product-family reference issued by Neo Plast Chem for buyer convenience. It is not a certificate of analysis. Figures are indicative/placeholder pending grade-specific lab verification and will be updated with certified values. For a batch-specific COA/SDS, or pricing and availability, contact our sales team.